

Powered Rakes**SR2672 & SR2690 Skid Steer Rakes**

| | SR2672 | SR2690 |
|-------------------------------------|--|----------------------------|
| Hydraulic Drive Requirements | 11 GPM at 2200 psi minimum | 15 GPM at 2500 psi minimum |
| Non-Angled Width | 82" | 100" |
| Non-Angled Working Width | 72" | 90" |
| Non-Angled Length | 63" | 81" |
| Overall Height | 41" | 41" |
| Machine Weight | 930 lbs. | 1200 lbs. |
| Direction of Travel | Bi-directional | |
| Material Control Blade | 2 each - 1/2" x 5" Urethane | |
| Spike Roller RPM | 9 3/8" Dia. with 3/4" x 1 1/2" Carbide Tipped Studs | |
| Roller Speed | Variable from 180 - 260 RPM | |
| Roller End Bearings | Roller Bearings | |
| Drive Chain | #50 Double Continuous Roller Chain, High Tensile, Enclosed in oil bath | |
| Angle Adjustment | Hydraulically controlled 18 degrees right and 22 degrees left | |
| Angle Cylinder | 2" X 8" | |
| Depth Control | 2 Each 16.5" x 6.5" Air Tires W/ sealant and 3/4" Roller bearings and Spacer height adjustment | |
| Skid Shoes | Replaceable | |
| Chain Case Lubrication | 2 1/2 pints of 80-90 weight Gear Lube - Add gear lube until it escapes from lower plug hole. | |